



(Indicative Picture)

## Specifications ...

<b>PUMP</b>		
Type		semitrash
Head	m	26
Flow	l/min	930
Revolution	RPM	3600
<b>ENGINE</b>		
Model		Honda
Type		GX160
Displacement	CC	163
Cylinder		1 Inclined
Power	kW	4.1
Fuel		Unleaded Petrol
Aspiration		Natural
Cooling System		Air
Starting System		Recoil
<b>CONSUMPTION</b>		
Consumption	g/kWh	313
Consumption at 75%	l/h	1.4
Tank Capacity	l	3.6
Running time at 75%	h	2.5
<b>NOISE EMISSION</b>		
Noise level LWA	dB(A)	105
Acoustic pressure at 7m	dB(A)	80
<b>DIMENSIONS AND WEIGHT</b>		
Length	mm	525
Width	mm	399
Height	mm	476
Input / Output diameter	inch	3
Weight (Dry)	kg	34
<b>STANDARD EQUIPMENT</b>		
Oil-guard system		•
3 jubilrr pipe clips		•
2 threaded coupling		•
Filter		•
Spark plug tool		•
<b>ACCESSORIES</b>		
Inlet pipes 2",3"		•
Length 8/25 m		•
Outlet pipe 2",3" Length 5/10/50/100m		•