



(Indicative Picture)

## Specifications ...

<b>THREE PHASE POWER</b>		
Power COP/LTP	kVA	11.76
Voltage	Volt	415
Frequency	Hz	50
<b>SINGLE PHASE POWER</b>		
Power COP/LTP	kVA	6.9
Voltage	Volt	240
Frequency	Hz	50
<b>ENGINE</b>		
Model		Honda
Type		GX620
Displacement	CC	614
Cylinder		2V
Speed	RPM	3000
Power	kW	14
Fuel		Unleaded
Aspiration		Natural
Cooling Systems		Air
Starting System		Electric
<b>CONSUMPTION</b>		
Consumption	g/kWh	313
Consumption at 75%	l/h	3.8
Fuel Tank Capacity	l	11
Running time at 75%	h	2.9
<b>NOISE EMISSION</b>		
Noise Level LWA	dB(A)	-
Acoustic Pressure at 7m	dB(A)	-
<b>DIMENSION &amp; WEIGHT</b>		
Length	mm	830
Width	mm	490
Height	mm	570
Weight (Dry)	kg	101
<b>STANDARD EQUIPMENT</b>		
Thermal Protection		*
Oil-Guard System		*
Magneto thermal protection		*
Battery charger (12V 10A)		*
Sockets		3 x 240V 16A 1 x 415V 16A
<b>PROTECTION</b>		
Electric Protection		IP23
Socket Protection		IP44
<b>ACCESSORIES</b>		
Transportation kit		*
Isometer protection		*
AMF		*