


**Specifications ...**

(Indicative Picture)

**ALTERNATOR**

Frequency	Hz	50
Output Rating	Continuous	100
(kVA)	Standby	110
No. of Phases	Three-Phase, 4 Wire	
Rated Voltage	V	Line to Line 50Hz: 190-240(240) or 380-415
Power Factor	0.8	
Voltage Regulation	%	Within + 0.5
Excitation	Brushless, Rotating Exciter (with A.V.R.)	
Insulation	Class F	

**ENGINE**

Make & Model	Komatsu SA6D102E-1-A	
Type	Inlined, Direct Injected Turbocharged, Aftercooled	
Output Rating		
	PS/rpm	133 / 1500
	KW/min-1	97.8 / 1500
No. of Cylinders-Bore X Stroke	mm	6 - 102 x 120
Piston Displacement	L	5.88
Fuel	Diesel	
Fuel Consumption	L/H	15.5
Lube Oil Sump Cap	L	22
Coolant Capacity	L	23.9
Battery Capacity	V-Ah	95E41RX2
Fuel Tank Capacity	L	250

**UNIT**

Dimensions (mm)	Length	3000
	Width	1080
	Height	1500
Dry Weight	Kg	2120

**SOUND LEVEL**

7m/dB (A) 1500rpm	(min-1)	63
-------------------	---------	----

**PH: 1300 302 991**