



(Indicative Picture)

**Specifications ...**
**ALTERNATOR**

Frequency	Hz	50
Output Rating	Continuous	12.5
(kVA)	Standby	13.8
No. of Phases		Three-Phase, 4 Wire
Rated Voltage	V	Line to Line 50Hz: 190-240(240) or 380-415
Power Factor		0.8
Voltage Regulation	%	Within + 0.5
Excitation		Brushless, Rotating Exciter (with A.V.R.)
Insulation		Class F

**ENGINE**

Make & Model		Kubota D1703-KB
Type		Inlined, Swirl Chambered
Output Rating		
	PS/rpm	13.8 / 1500
	KW/min-1	12.4 / 1500
No. of Cylinders-Bore X Stroke	mm	3 - 87 x 92.4
Piston Displacement	L	1.647
Fuel		Diesel
Fuel Consumption	L/H	2.8
Lube Oil Sump Cap	L	5.6
Coolant Capacity	L	6.4
Battery Capacity	V-Ah	80D26RX1
Fuel Tank Capacity	L	62

**UNIT**

Dimensions (mm)	Length	1390
	Width	650
	Height	900
Dry Weight	Kg	516

**SOUND LEVEL**

7m/dB (A) 1500rpm	(min-1)	60
-------------------	---------	----

**PH: 1300 302 991**