



T20 - 18,000L Fuel Tank

- Unit is supplied complete with a self bunded, packed dangerous goods storage area with locking container style doors. Storage area is weatherproof. Galvanised grated floor
- 6mL x 2.5mW x 2.75mH
- Bare Tank Weight 8 500 kg
- Safe fill level 18 000 litres
- 3" Camlock Male Tanker hose filler c/w Dust Cap connection
- Tanker fill point supplied c/w 80nb Full Bore, 2 piece, Fire Safe Flanged Ball Valve, and Wafer Style Non Return Valve
- Corner container lock castings
- CSC Plated as a 20ft Standard Shipping Container
- Overfill protection supplied with mechanical shutoff, and audible / visual alarm
- Antisyphon valve
- Permanent ladder and platform for ease of inspection and access
- Containment compartment (internal bunding) with pressure vent
- Bunded pump bay housing
- Air breather vents and fittings supplied complete with dust filter fitting
- Calibrated Fluid level dipstick
- Unit sandblasted to SA2
- Paint coating is Hempel Hemptane 55100 Colour Code 10 000. Primer coating is Hempel Hemptadur 15560 colour code 1217.
- Front mounted security doors c/w container lock handles
- Statutory signage
- Designed and manufactured in accordance with Australian Standards AS1940 and AS1692, Underwriters Laboratories standard UL 142 (USA) and Underwriters Laboratories standard ULC/ORD-142.18 (Canada)

