



(Indicative Picture)

**Specifications ...**
**ALTERNATOR**

Frequency	Hz	50
Output Rating	Continuous	20
(kVA)	Standby	22
No. of Phases	Three-Phase, 4 Wire	
Rated Voltage	V	Line to Line 50Hz: 190-240(240) or 380-415
Power Factor	0.8	
Voltage Regulation	%	Within + 0.5
Excitation	Brushless, Rotating Exciter (with A.V.R.)	
Insulation	Class F	

**ENGINE**

Make & Model	Isuzu AA-4LE2	
Type	Inlined, Direct Injected	
Output Rating		
	PS/rpm	26 / 1500
	KW/min-1	19.1 / 1500
No. of Cylinders-Bore X Stroke	mm	4-85 x 96
Piston Displacement	L	2,197
Fuel	Diesel	
Fuel Consumption	L/H	3.3
Lube Oil Sump Cap	L	8.5
Coolant Capacity	L	6.6
Battery Capacity	V-Ah	80D26RX1
Fuel Tank Capacity	L	70

**UNIT**

Dimensions (mm)	Length	1540
	Width	680
	Height	900
Dry Weight	Kg	564

**SOUND LEVEL**

7m/dB (A) 1500rpm	(min-1)	59
-------------------	---------	----

**PH: 1300 302 991**