


Specifications ...

(Indicative Picture)

ALTERNATOR

Frequency	Hz	50
Output Rating	Continuous	50
(kVA)	Standby	55
No. of Phases		Three-Phase, 4 Wire
Rated Voltage	V	Line to Line 50Hz: 190-240(240) or 380-415
Power Factor		0.8
Voltage Regulation	%	Within + 0.5
Excitation		Brushless, Rotating Exciter (with A.V.R.)
Insulation		Class F

ENGINE

Make & Model		Hino W04D-TG
Type		Inlined, Direct Injected Turbo
Output Rating		
	PS/rpm	66 / 1500
	KW/min-1	48.5 / 1500
No. of Cylinders-Bore X Stroke	mm	4 - 104 x 118
Piston Displacement	L	4.009
Fuel		Diesel
Fuel Consumption	L/H	8.8
Lube Oil Sump Cap	L	16.5
Coolant Capacity	L	12.2
Battery Capacity	V-Ah	80D26RX2
Fuel Tank Capacity	L	125

UNIT

Dimensions (mm)	Length	2050
	Width	880
	Height	1250
Dry Weight	Kg	1240

SOUND LEVEL

7m/dB (A) 1500rpm	(min-1)	61
-------------------	---------	----

PH: 1300 302 991